

Data sheet

Product designation

SOLO 800 B

120 V / 50-60 Hz

Article no. 51.010.00

230 V / 50-60 Hz

Article no. 51.011.00

Product description

Monolight with patented bayonet, 300 J / 300 Ws flash energy, control range continuous over 3 f-stops with rotary knob, built-in infrared sensitive photocell (can be switched off), proportional or full modelling light, internal discharge when power is reduced, dim function of the modelling light.

Scope of delivery

Unit with flash tube, modelling lamp, protecting glass, mains cable and protection cap for transport, operating instructions.

Technical data

Flash energy	300 J / 30 Ws
F-stop at 1 m (3.28 feet), (100 ISO, standard reflector)	45
Flash duration t 0.5	1/800 s
Charging time (for 100 % of selected energy)	230 V / 50 Hz: 0.6 – 1.4 s 120 V / 60 Hz: 0.6 – 1.4 s
Ready display	visual at 100 % of selected energy
Control range of flash energy	continuous over 3 f-stops
Modelling light	Halogen 150 W
Flash release	Synchronous cable, infrared sensitive* photocell (can be switched off), manual release button (test button)
Stabilized flash voltage	+/- 1 %
Power requirements	200-240 V, 50 Hz, 6 A 110-120 V, 60 Hz, 10 A
Standards	EC standard 73/23, UL 122
Cooling	fan
Dimensions	120 x 195 x 410 mm / 4.7 x 7.6 x 16 in.
Weight	2.4 kg / 5.38 lbs.

*) The infrared-sensitive photocell of the SOLO units reacts to a small amateur flash with a dark red filter placed in front of it.

Data sheet

Compatibility

Light shapers all VISATEC light shapers

Remote release VISATEC flash trigger

Special feature

If the monolight SOLO 800 B is used for longer flash sequences, we recommend that the flash tube for SOLO 1600 B should be employed.

Accessories

Flash tube, coated for SOLO 800 B	art. no. 54.300.00
Flash tube, coated for SOLO 1600 B	art. no. 54.301.00
Halogen modelling lamp (150 W / 230 V)	art. no. 54.252.XX
Halogen modelling lamp (150 W / 120 V)	art. no. 54.251.XX
Protecting glass, clear	art. no. 54.400.59
Fuse 3.15 AF	art. no. 37137.00
Protection cap for transport, grey	art. no. Z6098.00
Mains cable Europe 200-240 V	art. no. 39086.00
Mains cable CH 200-240 V	art. no. 39084.00
Mains cable USA 100-120 V	art. no. 39085.00
Synchronous cable	art. no. 54.104.00