

Data sheet

Product designation

Lightbar 120 Evolution

Article no. 32.353.XX

Product description

Light with dimensions 112 x 12 cm, can be operated at up to 2 x 3200 J, "tunnel-shaped" plexiglass diffuser, sheet steel back with cable outlet, 5 meter cable, modelling light switch, and separate interchangeable tilt head.

Scope of delivery

Lightbar with two cables, flash tubes, modelling lamps and interchangeable tilt head.

Technical data

Flash energy	2 x 3200 J
F-stop at 2 m, 100 ISO	45 5/10
Modelling light 220 V	20 x 20 W / 24 V
110 V	20 x 20 W / 12 V
Cable length	2 x 5 m
Cooling	2 fans
Dimensions	112 x 12 x 13 cm
Weight	6.8 kg

Compatibility

Power packs	Grafit 2, 4, A2, A4, A2 RFS, A4 RFS, A8 RFS, A2 plus, A4 plus, Topas A2, A4, A8 Nano2, Mobil Pulso 2, A2, 4, A4, Opus 2, A2, 4, A4, A8, Primo, Primo A, Primo A fashion, Primo 4,
-------------	---

For heat-related reasons, it is not possible to equip the Lightbar with a proportional halogen modelling lamp matching the other lamps.

Accessories

- Art. no. 33.271.00 Plexi cap transparent for Lightbar 120
- Art. no. 33.229.00 Barn door for Lightbar/Striplite 120
- Art. no. 33.275.00 Striplite adapter for Lightbar 120
- Art. no. 33.218.00 Honeycomb grid for Striplite 120

Application

Background gradations and general gradations - Automobile and bus lighting - Mirror projection of lines - Outlining contours and edges - Deep objects (depth) as in cupboards, deep-freezers, car boots etc. can be lit in the simplest way - Several Lightbars can be placed together for uninterrupted lighting - Simple and versatile mounting with the interchangeable tilt head - The possibility of transforming the Lightbar into a Striplite increases the application range.