

Product designation

Picolite small lamp

Article no. 32.020.00

Product description

Small lamp with built-in reflector. Small dimensions and little weight for tabletops and mobile work. Plug-in flash tube with spring fastener. Own accessories with small dimensions. Using the Pulso adapter, lightweight reflectors and accessories from the Pulso assortment may be applied. Switch and fuse for modelling lamp. Built-in tilt head with adjustable lever and umbrella holder. Fan for long series of flashes. Suitable for use with 100 V - 240 V voltages due to the stabilized supply voltage for the cooling fan. Thermal protection. UV-coated protecting glass. Handle. Max. 1600 J. Compatible with the battery-operated power pack Mobil (without modelling light when operating with battery).

Scope of delivery

Lamp without flash tube, modelling lamp, protecting glass

Technical data

Flash energy	max. 1600 J
f-stop at 2m (6 ½ ft.) distance, 100 ISO	1200 J: 22 4/10 with lamp angle 130° 1600 J: 22 9/10 with lamp angle 130°
Modelling light (fuse value)	150 W Halogen (3.15 AF)
Length of cable	3.5 m (11.4 ft.)
Cooling	fan stabilized
Dimensions	overall 205x135 mm, diameter 80 mm
Weight with cable	1.25 kg
Stand adapter	for bolts broncolor and Manfrotto 16 mm

Accessories

Attachment with 3 honeycomb grids and 2 aperture plates to Mobilite and Picolite	art. no. 33.204.00
Barn door with 4 wings to Mobilite and Picolite	art. no. 33.244.00
Pulso adapter to Mobilite and Picolite	art. no. 33.501.00

Data sheet

Fresnel spot attachment to Picolite and Mobilite	art. no. 33.631.00
Projection attachment 100 mm to Picolite	art. no. 33.641.00
Halogen modelling lamp 230 V / 150 W to Picolite	art. no. 34.201.00
Halogen modelling lamp 120 V / 150 W to Picolite	art. no. 34.202.00
Flash tube 1600 J without UV-coating to Mobilite and Picolite	art. no. 34.308.00
Protecting glass 5500 K to Mobilite and Picolite	art. no. 34.332.55
Protecting glass 5500 K, mat, to Mobilite and Picolite	art. no. 34.335.55
Twin articulated arm to Mobilite and Picolite	art. no. 35.102.00
Stand clamp for twin articulated Picolite/Mobilite adapter to Satellite Evolution	Art. No. 32.912.00 art. no. 35.214.00

Compatibility

Power packs	Grafit 2, 4, A2, A4, A2 RFS, A4 RFS, A8 RFS, A2 plus, A4 plus, Nano 2, Mobil, Primo, Primo A, Primo A fashion, Primo 4, Pulso 2, A2, 4, A4, Opus 2, A2, 4, A4, A8, 304, 404 Server
Pulso accessories (with help of adapter)	P70, P65, P50, P45, P-Travel, conical snoot, P-soft, softlight reflector, Mini-HazyLight, Cumulite 2, Megaflex, Flooter S, Pulsoflex up to 80x80 cm Satellite Evolution (with adapter), all umbrellas
without adapter	Fresnel spot attachment, honeycomb, Spot attachment, Picobox

Special features

- For safety reasons, never operate the lamps without the protecting glass in place.
- The accessories are identical with those of the Mobilite.
- For thermal reasons the UV-coating is applied to the protecting glass.