

Product designation

Following spot Profil 15/42

Article no. 32.435.XX

Product description

The following spot "Profil 15/42" offers a very hard light and an infinitely adjustable light angle from 15° to 42° degrees. The light can be adjusted by the focusing device to sharp or unsharp. The aperture slide stage can be rotated through 360° and contains 4 masks which allow most shapes to be produced. The iris diaphragm which is supplied with the spot offers the projection possibility of a continuously adjustable circle of light with slight colour borders.

The Profil 15/42 can be operated with all power packs even with the older ones up to 3200J.

Scope of delivery

Housing with lens system, focusing device, 5 m lamp cable, U-bracket holder, iris diaphragm, colour filter holder, including flash tube and modelling lamp.

Colour correction filter for 5500 K and 5100 K.

Technical data

Power	max. 3200 J
Light angle adjustment	15° to 42°
F-stop in 2 m distance 100 ISO	90 (15°) / 45 3/10 (42°)
Modelling light (fuse value)	Halogen 650 W (3.15 AF) 200 – 240 V Halogen 250 W (3.15 AF) 100 – 120 V
Connection cable	5 m
Cooling	Fan stabilized
Dimensions	Without U-bracket: 689 x 303 x 255 mm With U-bracket: 689 x 303 x 555 mm
Weight with cable	13,8 kg
Stand adapter	for broncolor bolt 12 mm, 3/8"-thread and bolt 16 mm

Compatibility

Power packs Grafit 2, 4, A2, A4, A2 RFS, A4 RFS, A8 RFS, A2 plus, A4 plus,
Topas A2, A4, A8
Nano 2, Nano A4
Mobil
Primo, Primo A, Primo A fashion, Primo 4,
Pulso 2, 4, A2, A4
Opus 2, 4, A2, A4, A8,
304*, 404*, 404 Servor
* wiring modification may be necessary

Accessories

Flash tube (5900 K) 3200 J, with socket	Art. no. L 5746.01
Lamp extension cable 5 m	Art. no.151.00
Lamp extension cable 10 m	Art. no 34.152.00
Halogen modelling lamp 250 W 100-120 V with fuse (screw base)	Art.-no. 34.221.07
Halogen modelling lamp 650 W 220-240 V with fuse (plug in base)	Art.-no. 34.226.10
Senior stand AC	Art.-no. 35.110.00
Compuls stand AC	Art.-no. 35.113.00
Stand for super-boom on casters	Art.-no. 35.141.00
Pillar stand 215	Art.-no. 35.160.00

Special features

Swing-out holders for flash tube and modelling lamp, stand attachment for the most commercial stands, safety device for ceiling mounting, colour temperature can be adjusted by the correction filter to 5500 K and 5100 K.

Application

The following spot Profil 15/42 distinguishes itself because of its very hard directed light. He is ideal in the fields of fashion, still-life, interior and car-photography. In general, Profil can be used when a hard atmospheric light is needed or projections with higher brightness. Because of the large diameter of the lens the light output is high but the projection shows slight colour fringing in the border area.