

### **Product designation**

**Reflector Satellite Evolution  
with bracket**

Article no. 33.150.00

### **Product description**

The reflector "Satellite" is a special light source with a high light output, a very narrow light angle, well directed light and very high f-stops (3200 J, 100 ISO, 2 m = 180 7/10; 30 m = 16 6/10). The adjustable lamp base allows different light angles. The lamp base with the special additional reflector reduces the amount of stray light to a minimum and furthermore increases the light output. The panels can be attached, with the clips, on the edge of the Satellite reflector. Satellite can be operated with the lamp bases Pulso G, Pulso F2/F4, Minipuls C40, C80, C200, Minipuls D160 with adapter art. no. 35.229.00 as well as the continuous daylight source broncolor HMI F575.

### **Scope of delivery**

Reflector Satellite with bracket and lamp base holder, protecting glass mat "UVE" (5500 K), special additional reflector to Pulso G, Pulso F2/F4 and broncolor HMI F575 lamp base.

The Pulso G, Pulso F2/F4 or broncolor HMI F575 lamp base and the Minipuls C, Minipuls D160 compact units have to be ordered separately.

### **Technical data**

F-stop at 2 m, 100 ISO, 3200 J	180 7/10
F-stop at 30 m	16 6/10
Licht angle adjustment range	10°-20° (at 3 meters and beyond) ) 18°-30° (at 2 meters)
Weight	5.6 kg
Weight (w/o bracket)	4.35 kg
Dimensions	880 x 250 mm

### **Compatibility**

Lamp bases	Pulso G, Pulso F2/F4 Picolite, Mobilite
broncolor	HMI F575
Compact units	Minipuls D160, Minipuls C40, C80, C200

### **Accessories**

Senior stand AC	Art.-Nr. 33.110.00
Compuls stand AC	Art.-Nr. 35.113.00
Pillar stand 215	Art.-Nr. 35.160.00
Adapter to Minipuls C / Minipuls D	Art.-Nr. 35.229.00

The holder for Satellite bracket to Hazylight/Flamingo stands (art. no. 35.218.00) is also compatible to the mentioned stands.

### **Special features**

The correspondence of the modelling light and the flash is ensured by focusing the F-lamp bases.

When operating with a Pulso F2- respectively Pulso G-lamp base with a coated flash tube, ensure that a protecting glass "mat" without coating (5900 K) is applied.

### **Application**

Satellite qualifies itself through hard, well directed light as well as a high light output. Therefore all ranges of advertising photography, especially fashion, still-life and food photography, are possible. The illumination is homogen and is distinguished by its soft edges.