



35mm tot tube diameter.

Wide base with double leg braces for added stability and safety.



3/8" microphone top fitting.



Complete with grip collar that allows the stand to be set at the required height with single operation.

Lightweight rubber base reducing "bottom end" frequencies being transmitted through the stand.



**ALU MICROPHONE STAND 622B**



195cm 108cm 2,7kg 2kg Type 36

Aluminium microphone stand.



**STEEL MICROPHONE STAND 622CS**



195cm 108cm 3,2kg 2kg Type 36

Chrome steel microphone stand.

**MICROPHONE CLIP MICC1**



0,05kg



Standard type microphone clip.

**TABLE TOP TRIPOD 209B**



4,5cm 13cm 13cm 0,09kg 2kg



Small and portable, this table top tripod complete with 3/8" top attachment for microphone fits into any small holdall ready to give quick support, in any location. Supplied without microphone holder.

**MICROPHONE SPRING CLIP MICC2**



0,05kg



Universal type microphone clip. Grabs microphones from diameter 20mm to 35mm.

**UNIVERSAL SHOCK MOUNT MICROPHONE HOLDER MICC4**



0,121kg



Made in aluminium supplied with a rubber dampening system to prevent shocks and vibrations. This rubber system allows efficient rapid microphone mounting. The swiveling yoke has a 3/8" threaded hole that allows convenient mounting to the range of carbon fiber microphone booms. Accepts a large variety of microphones.



**LE LOW STAND 602BSM**

-  125cm
  205cm
  104cm
  118cm
  5,7kg
-  50kg
  18kg@205cm
  35mm
  109, 110, 110G

Black chrome plated steel stand.  
 2 sections, 1 riser.  
 Ø: 40 - 35mm.  
 Leg Ø: 22mm.



**LE SELF LOCK STAND 256BMUAC**

-  109cm
  218cm
  106cm
  126cm
  2,5kg
-  20kg
  10kg@218cm
  35mm
  109, 110, 110G

Black steel base, aluminium sections, air cushioned stand.  
 2 sections, 1 riser.  
 Ø: 40, 35mm.  
 Leg Ø: 22mm.  
 1 levelling leg.  
 SELF LOCK SYSTEM PATENTED



**LE LEVELLING LEG STAND 126BMUAC**

-  106cm
  218cm
  106cm
  126cm
  2,5kg
-  30kg
  10kg@218cm
  35mm
  109, 110, 110G

Black aluminium stand, air cushioned.  
 2 sections, 1 riser.  
 Ø: 40, 35mm.  
 Leg Ø: 22mm.  
 1 levelling leg.



### LE MIDI STAND 604BSM

 154cm  
  260cm  
  132cm  
  126cm  
  6,6kg

 40kg  
  10kg@260cm  
  35mm  
  109, 110, 110G

Chrome plated steel stand.  
 2 sections, 1 riser.  
 Ø: 40 - 35mm.  
 Leg Ø: 22mm.



### LE MAXI STAND 606BSM

 182cm  
  316cm  
  160cm  
  126cm  
  7,2kg

 40kg  
  3kg@316cm  
  35mm  
  109, 110, 110G

Chrome plated steel stand.  
 2 sections, 1 riser.  
 Ø: 40 - 35mm.  
 Leg Ø: 22mm.



**PAN SPIGOT M10  
616-10**

Rotating 28mm spigot with M10 screw attachment. Smooth rotation is assured by a Teflon bearing. Complete with locking knob to block panoramic position.



**PAN SPIGOT M12  
616-12** Not illustrated

Same as 616-10 with M12 screw attachment.

**STAND TOP M10  
611-10**

M10 Bolt fixing for 32/38mm tube.

**STAND TOP M12  
611-12** Not illustrated

Same as 611-10 with M12 screw.

**LE 16MM ADAPTER  
623**

Designed to fit speaker stands, it forms a top fixing which mounts luminaires that have a 16mm spigot. Fits top tubes with diameters between 32mm and 38mm.

**28MM ADAPTER  
617**

Designed to fit speaker stands, it forms a top stand fixing which mounts luminaires with a 28mm spigot. Fits top tubes with diameters between 32mm and 38mm.



## SPEAKER ADAPTER FOR 28MM BUSHING 618

This speaker adapter (35mm diameter) can be mounted on all lightstands equipped with a 28mm bushing.




## SPEAKER ADAPTER FOR STAND 619

Female adapter equipped with 35mm stud for stands with top tube diameter between 32mm and 38mm.



## TILTING SPEAKER ADAPTER 624

Designed to be mounted onto tubes from 32mm to 38mm diameter. It is equipped with a 35mm speaker stud tilting from 0° to 20°.



## CABINET FITTINGS 612

Ramsa / Bose universal adaptor for 32/38mm tube.



## SAFETY COLLAR 35MM 698

Secondary safety system for all speaker stands. When locked into position, it stops upper stand sections from dropping when you open the stand locking knob.

