



Lighting booms provide the ideal unobtrusive way to position lighting and reflector equipment directly above the subject. The incredible number and variety of flash and continuous lights used, as well as their positioning requirements, have quickly made this range one of our most comprehensive lines.

We also have a wide selection of accessories available for customizing booms and make them easier to use.



Contents	Page
Lighting Booms	62
Lighting Booms Accessories	66

Boom arms allow you to position your lights in the most difficult positions.

Strong steel or tubular aluminium construction; counterweighted for smoothness of operation and stability.

Our considerable range allows you to choose the length, load capacity and support type that suits you, whether you're working from the ground on lighting stands, or directly from the wall or ceiling.



MEGA BOOM (STAND NOT INCLUDED) 425B

-  15kg
-  6kg*
-  GC
-  16mm/28mm

Largest boom in the range, remote control of pan, tilt and rotation of laminar plus geared telescopic extension. Combination of black zinc steel and black anodised aluminium tubes. 2 sections (Ø: 45, 55mm). Folded length: 220cm. Supplied with carrying bags. Min. extension from stand attachment: 50cm. Max. extension from stand attachment: 320cm. Suggested stand: Wind-Up series. * 6kg at maximum extension.



BLACK LIGHT BOOM (STAND NOT INCLUDED) 085BSL

-  8,9kg
 -  6kg*
 -  U
- Type 25 + Spigot Art. 013

Ø 35mm. 3 section boom arm complete with Pivoting Clamp 123, Counter Weight 022, cable clips and locking key. Load: 6kg at 230cm with 20kg of counter weight. Weight: 2.2kg, boom only. Dismantled length: 100cm. Assembled: 280cm. * 6kg at maximum extension.



BLACK SUPER BOOM (STAND NOT INCLUDED) 025BSL

-  10,8kg
 -  5kg*
 -  U
- Type 17 + Rapidapter Art. 014-38

Ø 35mm. 1 section boom complete with Pivoting Clamp 123, Counter Weight 022, cable clips. Load: 5kg at 200cm with 20kg of counter weight. Weight: 4.1kg, boom only. Remote control of lighting movement. 270cm long. * 5kg at maximum extension.



**BLACK LIGHT BOOM
(STAND INCLUDED) 085BS** Not illustrated



16,4kg Type 25 + Spigot Art. 013

Ø 35mm 3 section boom arm complete with Pivoting Clamp 123, Counter Weight 022, Cine Stand with casters, cable clips and locking key.
Load: 6kg at 230cm with counter weight. Weight: 2.2kg, boom only. 16.4kg including stand.
Dismantled length: 100cm. Assembled: 280cm.



**BLACK SUPER BOOM
(STAND INCLUDED) 025BS** Not illustrated



21kg Type 17 + Rapidapter Art. 014-38

Ø 35mm 1 section boom arm complete with Pivoting Clamp 123, Counter Weight 022, Cable Clips and Cine Stand 008 with casters.
Load: 5kg at 200cm with 20kg of counter weight. Weight: 4.1kg, boom only. Remote control of lighting movement.
270cm long.



LIGHT BOOM (STAND NOT INCLUDED) 024B



5,7kg Type 25 + Spigot Art. 013

Boom attaches to the shaft of most lightstands with diameters of 19, 20, 25, 28mm.
 Ø: 25mm 3 sections boom arm complete with Pivoting Clamp 124, Counter Weight 023, cable clips and locking key.
 Weight: 1.4kg (boom only). Load: 3kg at 170cm with counter weight.
 Dismantled length: 71cm. Assembled length: 200cm



Wall Bracket included

AUTOBOOM (STAND NOT INCLUDED) 254B



5,3kg Type 25 + Spigot Art. 013 + type 37

Boom arm for heavy stand or wall bracket mounting featuring self balancing spring system.
 Maximum load: 4kg at Maximum extension, 8kg at Minimum extension.
 Supplied with wall bracket.
 Minimum extension: 110cm. Maximum extension: 200cm.



SUPER BOOM WITH COLUMN STAND 025TM



18,5kg Type 17 + Rapidapter Art. 014-38

Ø 35mm. 1 section boom arm complete with Pivoting Clamp 123, Counter Weight 022, Cable Clips and Column Stand with casters.
 Load: 5kg at 200cm with 20kg of counter weight.
 Weight: 4.1kg, boom only. 140cm long.



WALL BOOM (STAND NOT INCLUDED) 098B



2,3kg Type 25 + Spigot Art. 013

Wall mounted boom arm. 2 section (Ø 35, 29mm).
 Rotation: 160° vertically and 180° horizontally.
 Load, at full extension: 4.5kg.
 Minimum extension: 120cm. Maximum extension: 210cm.



**SHORT WALL BOOM
(STAND NOT INCLUDED) 098SHB** Not illustrated



2kg Type 25 + Spigot Art. 013

Load: 5kg.
Minimum extension: 78cm. Maximum extension: 122cm.

MINI BOOM 173B



0,32kg Type 18 and Type 19

Boom shaft Ø: 20mm. Length: 109cm.

LONG MINI BOOM 173HOB Not illustrated

Long version of 173B. Length: 150cm.



G-PESO 022



6,7kg

Counterweight. Clamps on Ø 22mm to 35mm.



MINI COUNTER WEIGHT 172



1,3kg

Clamps on bars from Ø 13mm to 30mm.

L-PESO 023 Not illustrated



4,3kg





PIVOTING BOOM CLAMP 123

 0,72kg

Pivoting clamp for Ø 35mm boom shaft
Ø 28mm male and Ø 16mm attachment.



PIVOTING BOOM CLAMP 124

 0,67kg

Pivoting clamp for Ø: 19, 20, 25 and 28mm boom shafts
(or any tubes of these diameters).

BABY DROP DOWN PIN E700

 0,62kg  16mm  16mm



For a more accurate light positioning: it helps keeping the light in horizontal position independently on the angle of the boom. Specifically designed to be used on boom arm with light attachment with 16 mm pin.

AVENGER

JUNIOR DROP DOWN PIN E710

 1,32kg  Type 35  Type 34



Same as E700, designed to be used on boom arm with light attachment with 28 mm bushing.

AVENGER