

Product designation

Small lamp LP 1

Article no. 52.200.00

Product description

Lamp with built-in reflector and modelling lamp 12 V / 50 W to the battery-operated power pack LITEPAC. Plug-in flash tube with spring fastener. Small dimensions and little weight for mobile work. Large light angle. Own accessories with small dimensions. Switch and fuse for modelling lamp. Built-in tilt head with adjustable lever and umbrella holder. Fan for long series of flashes. Thermal protection. UV-coated protecting glass. Handle. Max. 1600 J.

Scope of delivery

Lamp with flash tube, modelling lamp, protecting glass

Technical data

| | |
|--|---|
| Flash energy | max. 1600 J |
| f-stop at 1 m (3 ¼ ft.) distance, 100 ISO | 600 J : 32 4/10 with lamp angle 130° |
| Modelling light (fuse value) | 12 V / 50 W Halogen (5 AF) |
| Length of cable | 3.5 m (11.4 ft.) |
| Cooling | fan 12 V, only switches on when necessary |
| Dimensions | overall 205x135 mm, diameter 80 mm |
| Weight with cable | 1.25 kg |
| Stand adapter | for standard bolts 16 mm |

Accessories

| | |
|--|--------------------|
| Fresnel spot attachment to LP 1 | art. no. 53.132.00 |
| Attachment with 3 honeycomb grids and 2 aperture plates to LP 1 | art. no. 53.203.00 |
| Barn door to LP 1 | art. no. 53.222.00 |
| Soloflex adapter to LP 1 | art. no. 53.458.00 |
| Lamp extension cable 3.5 m | art. no. 54.110.00 |
| Halogen modelling lamp 12 V / 50 W to LP 1 | art. no. 54.253.00 |
| Flash tube 1600 J without UV- coating LP 1 | art. no. 54.304.00 |
| Protecting glass 5500 K to LP 1 | art. no. 54.402.55 |

Data sheet

Twin articulated arm to LP 1 art. no. 55.110.00
Stand clamp to twin articulated arm art. no. 55.111.00
to LP 1

Compatibility

The small lamp LP 1 can only be used with the battery-operated power pack LITEPAC.

Special features

- For safety reasons, never operate the lamps without the protecting glass in place.
- For thermal reasons the UV-coating is applied to the protecting glass.