

### **Product designation**

**Transceiver RFS**  
(Radio Frequency System)

Article no. 56.202.00

### **Product description**

Radio transceiver with 10 digitally coded channels for wireless remote control and flash triggering of the visatec flash units containing an integrated RFS interface, from a PC or Macintosh computer. It has a dialogue function, that means, manual settings on the unit are automatically adjusted in the computer. The transceiver is contained in a plastic housing and has a USB connection cable as well as a sync cable. A base plate is fixed underneath the housing. The software is delivered on a data carrier. With digital camera systems which have a sync connection at the PC or Macintosh computer, the flash synchronization can be effected directly by means of the sync connector at the transceiver RFS. That means that there is no need for a separate RFS camera transmitter. The operational distance for power packs outdoors is up to 50 m; in closed rooms up to 30 m for compact units up to 30 m / 20 m. The transmission time is less then 1/1000 s. The transceiver is provided with a test button for the direct flash triggering and two buttons for the regulation of the output of all radio-controlled flash units in 1/1 or 1/10 f-stop increments. The computer supplies the unit with power. Therefore you do not need an additional energy source.

### **Scope of delivery**

Transceiver with base plate, 1 USB connection cable, 1 sync cable and 1 data carrier with software

### **Technical data**

Number of channels:	10
Operational distance outdoor:	up to 30 m / 50 m
Operational distance in closed rooms:	up to 20 m / 30 m
Dimensions (L x B x H):	80 x 55,5 x 51,5 mm (including base plate)
Weight:	tba
Trigger sequence per s:	10
Power supply:	from computer

### **Compatibility**

With this unit you can trigger visatec flash units with an integrated RFS interface.

### **Application**

For users of the digital system, whether Mac or PC, the transceiver RFS closes the gap to the completely computer controlled photograph. It is ideal for use in the studio as well as for outdoor photography. Its enormous range is very advantageous suitable for operation in large studios, on location and studios with non-reflective walls. Due to the digitally coded channels you can shoot in the same room from several work stations independently, without any interference between the flash units.

### **Arguments**

- Compatible with all RFS devices
- You can shoot in the same room from several work stations independently, without any interference between the flash units
- Computer control of the units via cable (PLUS)
- Handy and user-friendly unit with high breakage resistance - robust plastic housing, compact dimensions and low weight
- The large range gives the photographers a significant freedom of movement
- Operational distance outdoors 30 m / 50 m; in closed rooms up to 20 m / 30 m
- The computer supplies the unit with power. Therefore no additional energy source is necessary.